

## Foreman - Bug #1376

### Unattended installation without TFTP integration

12/07/2011 09:53 AM - Benjamin Papillon

|  |                           |
|--|---------------------------|
| <b>Status:</b> Closed  |                           |
| <b>Priority:</b> Normal  |                           |
| <b>Assignee:</b> Ohad Levy   |                           |
| <b>Category:</b> TFTP  |                           |
| <b>Target version:</b> 1.0   |                           |
| <b>Difficulty:</b>   | <b>Fixed in Releases:</b> |
| <b>Triaged:</b>  | <b>Found in Releases:</b> |
| <b>Bugzilla link:</b>  | <b>Red Hat JIRA:</b>      |
| <b>Pull request:</b>   |                           |
| <b>Description</b><br>With Foreman 0.4 on CentOS 5,<br><br>I do not use TFTP for Unattended installations. But foreman insists doing so.<br>If I configure a host and then click the "build" button, foreman tries to create the file<br>tftppath/mac-add-re-ss and it fails with the default install.<br>I created the tftppath directory under foreman root to bypass the problem.<br><br>Is there a cleanest way? |                           |

#### Associated revisions

##### Revision e51eda38 - 01/10/2012 03:50 PM - Ohad Levy

fixes #1376 - Unattended installation without TFTP integration

#### History

##### #1 - 12/20/2011 07:01 AM - Ohad Levy

- Target version set to 1.0

##### #2 - 01/10/2012 03:51 PM - Ohad Levy

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset [e51eda38e6e64c7b4d4622fbfb48eaa62143740b](#).