

Installer - Bug #15132

/etc/puppetlabs/puppetserver/bootstrap.cfg is missing in Puppet Server 2.5.0

05/23/2016 05:01 AM - Dominic Cleal

Status:	Closed	
Priority:	Normal	
Assignee:	Dominic Cleal	
Category:	Foreman modules	
Target version:	1.12.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/puppet-puppet/pull/402	

Description

puppet-puppet fails under Puppet Server 2.5.0 as it appears bootstrap.cfg is now gone:

```
# [ WARN 2016-05-23 08:48:00 verbose] /Stage[main]/Puppet::Server::Puppetserver/Augeas[puppet::server::puppetserver::jvm]/returns: executed successfully
# [ERROR 2016-05-23 08:48:00 verbose] /Stage[main]/Puppet::Server::Puppetserver/File_line[ca_enabled]: Could not evaluate: No such file or directory @ rb_sysopen - /etc/puppetlabs/puppetserver/bootstrap.cfg
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provider/file_line/ruby.rb:39:in `readlines'
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provider/file_line/ruby.rb:39:in `lines'
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provider/file_line/ruby.rb:6:in `exists?'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/property/ensure.rb:81:in `retrieve'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1068:in `retrieve'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1096:in `retrieve_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction/resource_harness.rb:221:in `from_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction/resource_harness.rb:19:in `evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction.rb:212:in `apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction.rb:228:in `eval_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction.rb:151:in `call'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction.rb:151:in `block (2 levels) in evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:386:in `block in thinmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/2.1.0/benchmark.rb:294:in `realtime'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:385:in `thinmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction.rb:151:in `block in evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/graph/relationship_graph.rb:118:in `traverse'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transaction.rb:142:in `evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/catalog.rb:222:in `block in apply'
```

```
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/log.
rb:155:in `with_destination'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on/report.rb:118:in `as_logging_destination'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/
catalog.rb:221:in `apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:171:in `block in apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:2
23:in `block in benchmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/2.1.0/benchmark.rb:294:in `r
ealtime'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:2
22:in `benchmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:170:in `apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:315:in `run_internal'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:186:in `block in run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.r
b:65:in `override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:240:in
`override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:185:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:350:in `apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:274:in `block in main'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.r
b:65:in `override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:240:in
`override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:225:in `main'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:170:in `run_command'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on.rb:344:in `block in run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:5
40:in `exit_on_fail'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on.rb:344:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/comm
and_line.rb:128:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/comm
and_line.rb:72:in `execute'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/bin/puppet:5:in `'
# [ERROR 2016-05-23 08:48:00 verbose] /Stage[main]/Puppet::Server::Puppetserver/File_line[ca_disa
bled]: Could not evaluate: No such file or directory @ rb_sysopen - /etc/puppetlabs/puppetserver/b
ootstrap.cfg
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provi
der/file_line/ruby.rb:39:in `readlines'
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provi
der/file_line/ruby.rb:39:in `lines'
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provi
der/file_line/ruby.rb:6:in `exists?'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/property/
ensure.rb:81:in `retrieve'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1
068:in `retrieve'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1
096:in `retrieve_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on/resource_harness.rb:221:in `from_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
```

```
on/resource_harness.rb:19:in `evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:212:in `apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:228:in `eval_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:151:in `call'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:151:in `block (2 levels) in evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:3
86:in `block in thinmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/2.1.0/benchmark.rb:294:in `r
ealtime'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:3
85:in `thinmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:151:in `block in evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/graph/rel
ationship_graph.rb:118:in `traverse'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:142:in `evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/
catalog.rb:222:in `block in apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/log.
rb:155:in `with_destination'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on/report.rb:118:in `as_logging_destination'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/
catalog.rb:221:in `apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:171:in `block in apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:2
23:in `block in benchmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/2.1.0/benchmark.rb:294:in `r
ealtime'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:2
22:in `benchmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:170:in `apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:315:in `run_internal'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:186:in `block in run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.r
b:65:in `override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:240:in
`override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:185:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:350:in `apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:274:in `block in main'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.r
b:65:in `override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:240:in
`override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:225:in `main'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:170:in `run_command'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on.rb:344:in `block in run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:5
40:in `exit_on_fail'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on.rb:344:in `run'
```

```
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/comm
and_line.rb:128:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/comm
and_line.rb:72:in `execute'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/bin/puppet:5:in `'
# [ERROR 2016-05-23 08:48:00 verbose] /Stage[main]/Puppet::Server::Puppetserver/File_line[version
ed_code_service]: Could not evaluate: No such file or directory @ rb_sysopen - /etc/puppetlabs/pup
petserver/bootstrap.cfg
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provi
der/file_line/ruby.rb:39:in `readlines'
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provi
der/file_line/ruby.rb:39:in `lines'
# [ INFO 2016-05-23 08:48:00 verbose] /usr/share/foreman-installer/modules/stdlib/lib/puppet/provi
der/file_line/ruby.rb:6:in `exists?'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/property/
ensure.rb:81:in `retrieve'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1
068:in `retrieve'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1
096:in `retrieve_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on/resource_harness.rb:221:in `from_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on/resource_harness.rb:19:in `evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:212:in `apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:228:in `eval_resource'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:151:in `call'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:151:in `block (2 levels) in evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:3
86:in `block in thinmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/2.1.0/benchmark.rb:294:in `r
ealtime'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:3
85:in `thinmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:151:in `block in evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/graph/rel
ationship_graph.rb:118:in `traverse'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on.rb:142:in `evaluate'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/
catalog.rb:222:in `block in apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/log.
rb:155:in `with_destination'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/transacti
on/report.rb:118:in `as_logging_destination'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/
catalog.rb:221:in `apply'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:171:in `block in apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:2
23:in `block in benchmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/2.1.0/benchmark.rb:294:in `r
ealtime'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:2
22:in `benchmark'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:170:in `apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:315:in `run_internal'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:186:in `block in run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.r
```

```
b:65:in `override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:240:in
`override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/configure
r.rb:185:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:350:in `apply_catalog'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:274:in `block in main'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.r
b:65:in `override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:240:in
`override'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:225:in `main'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on/apply.rb:170:in `run_command'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on.rb:344:in `block in run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:5
40:in `exit_on_fail'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/applicati
on.rb:344:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/comm
and_line.rb:128:in `run'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/comm
and_line.rb:72:in `execute'
# [ INFO 2016-05-23 08:48:00 verbose] /opt/puppetlabs/puppet/bin/puppet:5:in `'
# [ WARN 2016-05-23 08:48:00 verbose] /Stage[main]/Puppet::Server::Puppetserver/File[/etc/puppetl
abs/puppetserver/conf.d/ca.conf]/ensure: defined content as '{md5}89ee09574b369829999d72d8ec1e8b8e
'
```

/etc now contains:

```
/etc/puppetlabs/puppetserver
/etc/puppetlabs/puppetserver/conf.d
/etc/puppetlabs/puppetserver/conf.d/auth.conf
/etc/puppetlabs/puppetserver/conf.d/global.conf
/etc/puppetlabs/puppetserver/conf.d/puppetserver.conf
/etc/puppetlabs/puppetserver/conf.d/web-routes.conf
/etc/puppetlabs/puppetserver/conf.d/webserver.conf
/etc/puppetlabs/puppetserver/logback.xml
/etc/puppetlabs/puppetserver/request-logging.xml
/etc/puppetlabs/puppetserver/services.d
/etc/puppetlabs/puppetserver/services.d/ca.cfg
```

but on 2.4.0:

```
/etc/puppetlabs/puppetserver
/etc/puppetlabs/puppetserver/bootstrap.cfg
/etc/puppetlabs/puppetserver/conf.d
/etc/puppetlabs/puppetserver/conf.d/auth.conf
/etc/puppetlabs/puppetserver/conf.d/global.conf
/etc/puppetlabs/puppetserver/conf.d/puppetserver.conf
/etc/puppetlabs/puppetserver/conf.d/web-routes.conf
/etc/puppetlabs/puppetserver/conf.d/webserver.conf
/etc/puppetlabs/puppetserver/logback.xml
/etc/puppetlabs/puppetserver/request-logging.xml
```

Associated revisions

Revision 68c2d50e - 05/25/2016 05:03 PM - Dominic Cleal

fixes #15132 - support services.d/ configuration in Puppet Server 2.5 (#402)

PS 2.5 moves CA configuration from bootstrap.cfg to a services.d/ca.cfg file, separating user config (CA) from app config (e.g. versioned code service). This is now configured instead of bootstrap.cfg when the

server_puppetserver_version parameter is set to 2.5.

A special version value of 2.4.99 (now the default) configures both the 2.4 and 2.5 files simultaneously, creating both bootstrap.cfg and services.d/ca.cfg so the module works across both versions, albeit with logged warnings about duplicate CA definitions. This ensures the module will still work on the release of 2.5, after which time the parameter default can be changed to 2.5.0 to remove the duplicate configuration.

History

#1 - 05/23/2016 05:46 AM - Dominic Cleal

Related tickets:

<https://tickets.puppetlabs.com/browse/SERVER-1247>

<https://tickets.puppetlabs.com/browse/SERVER-1213>

#2 - 05/23/2016 11:14 AM - Dominic Cleal

Additionally the BOOTSTRAP_CONFIG has changed in /etc/sysconfig/puppetserver (or /etc/default) to:

```
BOOTSTRAP_CONFIG="/etc/puppetlabs/puppetserver/services.d/,/opt/puppetlabs/server/apps/puppetserver/config/services.d/"
```

from /etc/puppetlabs/puppetserver/bootstrap.cfg.

I think to retain compatibility with 2.4 and 2.5, we could:

1. specify all three directories (bootstrap.cfg, 2x services.d) in BOOTSTRAP_CONFIG
2. add a file resource to ensure bootstrap.cfg exists (for file_line)
3. add a file resource to ensure both services.d/ directories exist
4. use file_line on both bootstrap.cfg and ca.cfg

which appears to work on both 2.4 and 2.5, with it just logging some warnings about CA services being declared twice, in both bootstrap.cfg and ca.cfg. When 2.5's released then we could change the default behaviour to only configure ca.cfg and use the puppetserver version parameter to provide 2.4 compatibility.

#3 - 05/24/2016 03:48 AM - Dominic Cleal

- Status changed from New to Assigned

- Assignee set to Dominic Cleal

#4 - 05/24/2016 07:09 AM - Dominic Cleal

- Status changed from Assigned to Ready For Testing

- Pull request <https://github.com/theforeman/puppet-puppet/pull/402> added

#5 - 05/25/2016 06:01 PM - Dominic Cleal

- Status changed from Ready For Testing to Closed

- % Done changed from 0 to 100

Applied in changeset [puppet-puppet|68c2d50eac54de1e21e66a96794eca1d1d51f8af.](#)

#6 - 05/27/2016 04:46 AM - Dominic Cleal

- translation missing: en.field_release set to 136