

## Installer - Feature #21473

### Add loop-break statement for iPXE/gPXE

10/26/2017 07:50 AM - Lukas Zapletal

<b>Status:</b> New	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b>	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
We need to add this into dhcpd.conf:	
<pre>elseif exists user-class and (option user-class = "iPXE" or option user-class = "gPXE") {     filename "http://foreman/unattended/iPXE"; }</pre>	
So users don't need to set this manually. Note it must be HTTP (HTTPS will not work in iPXE environment). If this is parametrized, users should be able to set smart-proxy instead of foreman in this form: <a href="http://proxy:8000/unattended/iPXE">http://proxy:8000/unattended/iPXE</a>	
For more info: <a href="http://projects.theforeman.org/projects/foreman/wiki/Fetch_boot_files_via_http_instead_of_TFTP">http://projects.theforeman.org/projects/foreman/wiki/Fetch_boot_files_via_http_instead_of_TFTP</a>	