

Installer - Bug #22479

Installer fails when run with --foreman-proxy-plugin-discovery-install-images true

02/01/2018 09:49 AM - Marek Hulán

Status: Closed	
Priority: Normal	
Assignee: Ewoud Kohl van Wijngaarden	
Category: Foreman modules	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request: https://github.com/theforeman/puppet-foreman_proxy/pull/410	
Description	
When I run the installer like this	
<pre>foreman-installer --enable-foreman-plugin-discovery --enable-foreman-proxy-plugin-discovery --foreman-proxy-plugin-discovery-install-images true</pre>	
I get following error	
<pre>Could not find dependency File[/var/lib/tftpboot/boot] for Foreman::Remote_file[/var/lib/tftpboot/boot/fdi-image-latest.tar] at /usr/share/foreman-installer/modules/foreman_proxy/manifests/plugin/discovery.pp:29 /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/errors.rb:106:in `fail' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1511:in `block in validate_relationship' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1508:in `each' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:1508:in `validate_relationship' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:2531:in `block in finish' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:2529:in `collect' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/type.rb:2529:in `finish' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/catalog.rb:283:in `block in finalize' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/catalog.rb:283:in `each' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/resource/catalog.rb:283:in `finalize' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/application/apply.rb:265:in `block in main' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/context.rb:65:in `override' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet.rb:306:in `override' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/application/apply.rb:225:in `main' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/application/apply.rb:170:in `run_command' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/application.rb:358:in `block in run' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util.rb:662:in `exit_on_fail' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/application.rb:358:in `run' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/command_line.rb:132:in `run' /opt/puppetlabs/puppet/lib/ruby/vendor_ruby/puppet/util/command_line.rb:72:in `execute' /opt/puppetlabs/puppet/bin/puppet:5:in `<main>'</main></pre>	
The reason is that discovery puppet manifest relies on File resources which is not defined anywhere see https://github.com/theforeman/puppet-foreman_proxy/blob/master/manifests/plugin/discovery.pp#L32	
The File for directory creation should probably be defined at https://github.com/theforeman/puppet-tftp/blob/master/manifests/config.pp or in discovery itself but I'm not entirely sure how exactly this should behave or why the require is there.	

Associated revisions

Revision b3a811ce - 02/26/2018 05:58 PM - Ewoud Kohl van Wijngaarden

Fixes #22479 - Handle remote directory with undefined parent

This can happen when tftp is set to false or unmanaged.

We move the `remote_file` define to this module since puppet-foreman no longer uses it itself. That will allow us to remove it there in a next major release.

History

#1 - 02/20/2018 09:28 AM - Ewoud Kohl van Wijngaarden

I'm guessing you also disabled tftp management in a previous installer run. Is that correct?

#2 - 02/21/2018 05:31 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Ewoud Kohl van Wijngaarden
- Pull request https://github.com/theforeman/puppet-foreman_proxy/pull/410 added

#3 - 02/26/2018 06:01 PM - Ewoud Kohl van Wijngaarden

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [puppet-foreman_proxy|b3a811cefc2011dffb6fb1894a6fa98bc1df6724](#).