

## Installer - Feature #25190

### Allow overriding the tftpd.map source location

10/12/2018 02:46 PM - Ewoud Kohl van Wijngaarden

|   |   |                                  |
|---|---|----------------------------------|
| <b>Status:</b>  | Closed  |                                  |
| <b>Priority:</b>  | Normal  |                                  |
| <b>Assignee:</b>  | Ewoud Kohl van Wijngaarden  |                                  |
| <b>Category:</b>  | Foreman modules   |                                  |
| <b>Target version:</b>  | 1.20.0  |                                  |
| <b>Difficulty:</b>  |   | <b>Fixed in Releases:</b> 1.20.0 |
| <b>Triaged:</b>   | No  | <b>Found in Releases:</b>        |
| <b>Bugzilla link:</b>   | 1571889   | <b>Red Hat JIRA:</b>             |
| <b>Pull request:</b>  | <a href="https://github.com/theforeman/puppet-tftp/pull/82">https://github.com/theforeman/puppet-tftp/pull/82</a> |                                  |
| <b>Description</b>  |   |                                  |
| Currently the source of /etc/tftpd.map is hardcoded to puppet:///modules/tftp/tftpd.map. This means the user can't modify its content. Adding an option for that would give more flexibility. |   |                                  |

#### Associated revisions

**Revision 56276e2d - 10/15/2018 11:40 AM - Ewoud Kohl van Wijngaarden**

Fixes #25190 - Allow overriding the tftp map source

#### History

**#1 - 10/12/2018 02:48 PM - The Foreman Bot**

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/puppet-tftp/pull/82> added

**#2 - 10/15/2018 12:01 PM - Ewoud Kohl van Wijngaarden**

- Status changed from Ready For Testing to Closed

Applied in changeset [puppet-tftp|56276e2dde05db3f7bc3c04e756565d9daadad42](#).

**#3 - 10/17/2018 08:52 AM - Tomer Brisker**

- Fixed in Releases 1.20.0 added