

## Installer - Bug #27124

### Parameter foreman-proxy-content-pulp-admin-password invalid: false is not a valid string

06/25/2019 09:32 AM - Sven Vogel

<b>Status:</b>	Resolved	
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>	foreman-installer script	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>	No	<b>Found in Releases:</b> 1.21.3
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>		

#### Description

After new install of foreman-proxy with katello i get the following error.

foreman: 1.21.3  
katello: 3.11.1

```
foreman-installer --scenario foreman-proxy-content\  
> --certs-tar-file "/root/katello-smart-proxy-xx.  
example.de-certs.tar"\  
> --foreman-proxy-content-parent-fqdn "katello01.example.de"\  
> --foreman-proxy-register-in-foreman "true"\  
> --foreman-proxy-foreman-base-url "https://katello01.example.de"  
\   
> --foreman-proxy-trusted-hosts "katello01.example.de"\  
> --foreman-proxy-trusted-hosts "katello-smart-proxy-xx.exempl  
e.de"\  
> --foreman-proxy-oauth-consumer-key "doRmgp4tgVcSy7xkzbfz2wJxYM4CN  
nXx"\  
> --foreman-proxy-oauth-consumer-secret "fDsqtg5k5XHMERxxNQACUtFGrLKQy  
ZdW"\  
> --puppet-server-foreman-url "https://katello01.example.de"  
\
```

the following error occurs.

```
error:  
  
[ INFO 2019-06-25T11:27:41 verbose] Executing hooks in group pre_migrations  
[ INFO 2019-06-25T11:27:41 verbose] All hooks in group pre_migrations finished  
[ INFO 2019-06-25T11:27:41 verbose] Executing hooks in group boot  
[ INFO 2019-06-25T11:27:41 verbose] All hooks in group boot finished  
[ INFO 2019-06-25T11:27:41 verbose] Executing hooks in group init  
[ INFO 2019-06-25T11:27:41 verbose] All hooks in group init finished  
[ INFO 2019-06-25T11:27:41 verbose] Loading default values from puppet modules...  
[ INFO 2019-06-25T11:27:41 verbose] ... finished  
[ INFO 2019-06-25T11:27:41 verbose] Executing hooks in group pre_values  
[ INFO 2019-06-25T11:27:41 verbose] All hooks in group pre_values finished  
[ INFO 2019-06-25T11:27:41 verbose] Running installer with args [{"--scenario", "foreman-proxy-con  
tent", "--certs-tar-file", "/root/katello-smart-proxy-xx.example.de-certs.tar", "--foreman-proxy-c  
ontent-parent-fqdn", "katello01.example.de", "--foreman-proxy-register-in-foreman", "true", "--for  
eman-proxy-foreman-base-url", "https://katello01.example.de", "--foreman-proxy-trusted-hosts", "ka  
tello01.example.de", "--foreman-proxy-trusted-hosts", "katello-smart-proxy-xx.example.de", "--fore  
man-proxy-oauth-consumer-key", "doRmgp4tgVcSy7xkzbfz2wJxYM4CNnXx", "--foreman-proxy-oauth-consumer  
-secret", "fDsqtg5k5XHMERxxNQACUtFGrLKQyZdW", "--puppet-server-foreman-url", "https://katello01.ex  
ample.de", "--verbose"]]  
[ INFO 2019-06-25T11:27:41 verbose] Executing hooks in group pre_validations  
[ INFO 2019-06-25T11:27:41 verbose] All hooks in group pre_validations finished
```

```
[ INFO 2019-06-25T11:27:41 verbose] Running validation checks
[ERROR 2019-06-25T11:27:41 verbose] Parameter foreman-proxy-content-pulp-admin-password invalid: false is not a valid string
[ERROR 2019-06-25T11:27:41 verbose] Parameter foreman-proxy-content-qpuid-router-sasl-password invalid: false is not a valid string
Error during configuration, exiting
```

after investigating the **foreman-installer --full-help** i get the following

```
--foreman-proxy-content-pulp-admin-password Password for the Pulp admin user. It should be left blank so that a random password is generated (current: false)
--reset-foreman-proxy-content-pulp-admin-password Reset pulp_admin_password to the default value (false)
```

and

```
--foreman-proxy-content-qpuid-router-sasl-password SASL password to be used from router to broker (current: false)
--reset-foreman-proxy-content-qpuid-router-sasl-password Reset qpuid_router_sasl_password to the default value (false)
```

i think it should be "UNDEF" or clear so that the installer can be create a own password.

## History

---

**#1 - 06/25/2019 11:41 AM - Sven Vogel**

- *Status changed from New to Resolved*

i found a solution.

it seems there is a problem if the "cache\_data" files exists with empty values.

so i removed the folder. it seems the function "cache\_data" delivers "false" if the value of any file like "pulp\_node\_admin\_password" within "foreman\_cache\_data" folder is empty.

```
rm -rf /opt/puppetlabs/puppet/cache/foreman_cache_data/
```

it will be recreated with random password.