

## Installer - Feature #28084

### Store altered defaults in hiera

10/17/2019 03:52 PM - Ewoud Kohl van Wijngaarden

<b>Status:</b> Ready For Testing	
<b>Priority:</b> Normal	
<b>Assignee:</b> Ewoud Kohl van Wijngaarden	
<b>Category:</b> foreman-installer script	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b> No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b> <a href="https://github.com/foreman/foreman-installer/pull/399">https://github.com/foreman/foreman-installer/pull/399</a>	
<b>Description</b> Currently the non-default values are stored in the answers file. The downside is that using <code>--reset-\$param</code> doesn't work as expected. Kafo 4 provides the scenario id in a fact which allows specifying another layer in hiera.yaml. Hiera is also always loaded (with answers only when needed). This allows using a proper reset. It also allows shipping non-default values for disabled modules.	

### History

#### #1 - 10/17/2019 03:55 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Ewoud Kohl van Wijngaarden
- Pull request <https://github.com/foreman/foreman-installer/pull/399> added