

Installer - Bug #28366

A useless default Apache vhost is shipped

11/26/2019 03:50 PM - Ewoud Kohl van Wijngaarden

Status:	Closed	
Priority:	Normal	
Assignee:	Ewoud Kohl van Wijngaarden	
Category:	foreman-installer script	
Target version:	2.0.0	
Difficulty:		Fixed in Releases: 2.0.0
Triaged:	Yes	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman-installer/pull/412	
Description puppetlabs-apache sets up a default vhost, but this isn't needed for our use case where we always deploy a vhost.		

Associated revisions

Revision a63f26e5 - 11/26/2019 05:06 PM - Ewoud Kohl van Wijngaarden

Fixes #28366 - Drop default Apache vhost

Apache always ships a default vhost in /etc/httpd/conf.d/15-default.conf (or Debian equivalent) that isn't used. Not enabling this will make the setup easier to understand.

History

#1 - 11/26/2019 03:53 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Ewoud Kohl van Wijngaarden
- Pull request <https://github.com/foreman/foreman-installer/pull/412> added

#2 - 11/26/2019 06:01 PM - Ewoud Kohl van Wijngaarden

- Status changed from Ready For Testing to Closed

Applied in changeset [installer\[a63f26e5c03ea0e7aadd87b2d80f3cffb163159d\]](#).