Installer - Bug #28559

Hardcoding Proxy Command breaks running Ansible on Debian

12/21/2019 09:51 PM - Marek Hulán

Status:	Closed		
Priority:	Normal		
Assignee:	Marek Hulán		
Category:	Foreman modules		
Target version:			
Difficulty:		Fixed in Releases:	2.0.0
Triaged:	No	Found in Releases:	
Bugzilla link:		Red Hat JIRA:	
Pull request:	https://github.com/theforeman/puppet-for eman_proxy/pull/554		
Description			
see https://projects.theforeman.org/issues/25481#note-11 for more details			
Related issues:			
Related to Ansible - Feature #31552: Adjust ssh_args defaults for better perf			Rejected
Related to Installer - Bug #25481: Foreman fails to execute ansible commands		Closed	

Associated revisions

Revision 557cb3f9 - 12/25/2019 09:02 PM - Marek Hulán

Fixes #28559 - keep default ssh args (#554)

Based on https://docs.ansible.com/ansible/latest/reference_appendices/config.html#ansible-ssh-args the ssh args is by default set to "-C -o ControlMaster=auto -o ControlPersist=60s". In

2e11f6810d8b4e7e8ce28f91bdf6a534c0f3e2f4, this was overridden to "-o ProxyCommand=none" only. There seems to be no way to just append arguments, so

listing defaults here is probably the best option.

History

#1 - 12/21/2019 09:56 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Assignee set to Marek Hulán

- Pull request https://github.com/theforeman/puppet-foreman_proxy/pull/554 added

#2 - 12/25/2019 09:02 PM - The Foreman Bot

- Fixed in Releases 2.0.0 added

#3 - 12/25/2019 10:01 PM - Anonymous

- Status changed from Ready For Testing to Closed

Applied in changeset puppet-foreman_proxy|557cb3f9da765786cf8962a4bb5b1ebe4cf11adf.

#4 - 12/24/2020 12:01 PM - Ondřej Ezr

- Related to Feature #31552: Adjust ssh_args defaults for better performance added

#5 - 10/31/2022 02:21 PM - Ewoud Kohl van Wijngaarden

- Related to Bug #25481: Foreman fails to execute ansible commands when connected to ipa server added