

## Installer - Bug #30211

### proxying pulp rpm/isos to pulpcore with pulpcore disabled disables pulp2 plugins

06/25/2020 12:04 AM - William Clark

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	William Clark	
<b>Category:</b>	Foreman modules	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 2.2.0
<b>Triaged:</b>	No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/theforeman/puppet-foreman_proxy_content/pull/265">https://github.com/theforeman/puppet-foreman_proxy_content/pull/265</a>	
<b>Description</b>		
The pulp class is declared in puppet-FPC with		
<pre>class { 'pulp':   ...   enable_rpm      =&gt; \$enable_yum and !\$proxy_pulp_yum_to_pulpcore,   enable_iso      =&gt; \$enable_file and !\$proxy_pulp_isos_to_pulpcore,   ...</pre>		
However \$proxy_pulp_{yum,isos}_to_pulpcore defaults to true, leading to these pulp2 plugins being disabled when running foreman-installer with `--foreman-proxy-plugin-pulp-pulpcore-enabled false`		

#### Associated revisions

**Revision 5d691aaf - 06/26/2020 10:08 AM - William Clark**

Fixes #30211 - don't disable pulp2 plugins when pulpcore disabled

#### History

**#1 - 06/25/2020 12:09 AM - The Foreman Bot**

- Status changed from New to Ready For Testing

- Pull request [https://github.com/theforeman/puppet-foreman\\_proxy\\_content/pull/265](https://github.com/theforeman/puppet-foreman_proxy_content/pull/265) added

**#2 - 06/26/2020 10:08 AM - The Foreman Bot**

- Fixed in Releases 2.2.0 added

**#3 - 06/26/2020 11:01 AM - William Clark**

- Status changed from Ready For Testing to Closed

Applied in changeset [puppet-foreman\\_proxy\\_content!5d691aaf7ba6aaafc1bf7a89110454eeca94b90b](https://github.com/theforeman/puppet-foreman_proxy_content/commit/5d691aaf7ba6aaafc1bf7a89110454eeca94b90b).