

Installer - Feature #30217

Configure Pulpcore database name with foreman-installer

06/25/2020 03:44 PM - William Clark

Status:	Closed	
Priority:	Normal	
Assignee:	William Clark	
Category:	Foreman modules	
Target version:		
Difficulty:		Fixed in Releases: 2.2.0
Triaged:	No	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/puppet-foreman_proxy_content/pull/266	
Description		
The Pulpcore database name is configurable in puppet-pulpcore but is not currently exposed in puppet-foreman_proxy_content		
Related issues:		
Related to Installer - Feature #28901: Support pulpcore db on remote hosts		Closed

Associated revisions

Revision 5af4601c - 06/25/2020 05:33 PM - William Clark

Fixes #30217 - configure pulpcore db name

History

#1 - 06/25/2020 03:54 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request https://github.com/theforeman/puppet-foreman_proxy_content/pull/266 added

#2 - 06/25/2020 05:33 PM - The Foreman Bot

- Fixed in Releases 2.2.0 added

#3 - 06/25/2020 06:01 PM - William Clark

- Status changed from Ready For Testing to Closed

Applied in changeset [puppet-foreman_proxy_content\[5af4601c273857835c0a313d417136d766045123](https://puppet-foreman_proxy_content[5af4601c273857835c0a313d417136d766045123).

#4 - 08/13/2020 10:20 AM - Ewoud Kohl van Wijngaarden

- Related to Feature #28901: Support pulpcore db on remote hosts added