

## Installer - Feature #33789

### Mark host where the installer is running as foreman when deploying foreman

10/26/2021 03:44 PM - Adam Ruzicka

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Adam Ruzicka	
<b>Category:</b>	Foreman modules	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 3.1.0
<b>Triaged:</b>	No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/theforeman/puppet-foreman/pull/965">https://github.com/theforeman/puppet-foreman/pull/965</a>	
<b>Description</b>		
<b>Related issues:</b>		
Related to Foreman - Tracker #32324: Distinguish between "regular" hosts and ...		<b>New</b>

#### Associated revisions

##### Revision 8889aad5 - 10/28/2021 12:53 AM - Adam Ruzicka

Fixes #33789 - Mark host where the installer is running as foreman

when deploying foreman.

This introduces three new resources. `foreman_host` represents a host record in Foreman. `foreman_instance_host` can be used to mark an already present `foreman_host` as a foreman instance. `foreman_smartproxy_host` works similarly, but marks an already present `foreman_host` as a host forming already existing `foreman_smartproxy`.

#### History

##### #1 - 10/26/2021 03:44 PM - Adam Ruzicka

- Related to Tracker #32324: Distinguish between "regular" hosts and hosts on which Foreman and/or smart proxy runs added

##### #2 - 10/26/2021 03:49 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/puppet-foreman/pull/965> added

##### #3 - 10/28/2021 12:53 AM - The Foreman Bot

- Fixed in Releases 3.1.0 added

##### #4 - 10/28/2021 01:01 AM - Adam Ruzicka

- Status changed from Ready For Testing to Closed

Applied in changeset [puppet-foreman|8889aad54336f7e4b791665d6a58d3afd79e94f1](#).