

## Installer - Bug #34882

### Pulp: Add options to change the import and export path in /etc/pulp/settings.py

05/09/2022 08:30 PM - William Clark

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b> William Clark	
<b>Category:</b>	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b> 3.3.0
<b>Triaged:</b> No	<b>Found in Releases:</b>
<b>Bugzilla link:</b> 2028446	<b>Red Hat JIRA:</b>
<b>Pull request:</b> <a href="https://github.com/theforeman/puppet-for-eman_proxy_content/pull/417">https://github.com/theforeman/puppet-for-eman_proxy_content/pull/417</a>	
<b>Description</b> Cloned from <a href="https://bugzilla.redhat.com/show_bug.cgi?id=2028446">https://bugzilla.redhat.com/show_bug.cgi?id=2028446</a>	
<b>Description of problem:</b>  [RFE] Add options to change the import and export path in /etc/pulp/settings.py	
<b>Version-Release number of selected component (if applicable):</b> satellite-6.10	
<b>How reproducible:</b> New installation	
<b>Actual results:</b>  There is no option available through custom-hiera.yaml or satellite-installer to change the below directories to custom path	
1. cat /etc/pulp/settings.py	
ALLOWED_IMPORT_PATHS = ["/var/lib/pulp/sync_imports", "/var/lib/pulp/imports"] ALLOWED_EXPORT_PATHS = ["/var/lib/pulp/exports"]	
It seems to be a hard-coded in the configuration :	
1. cat /usr/share/foreman-installer/modules/foreman_proxy_content/manifests/init.pp  grep -iE "sync_imports imports" \$pulpcore_allowed_import_path = ["/var/lib/pulp/sync_imports"] \$pulpcore_allowed_import_path = ["/var/lib/pulp/sync_imports", "/var/lib/pulp/imports"]	
1. cat /usr/share/foreman-installer/modules/pulpcore/templates/settings.py.erb	
ALLOWED_IMPORT_PATHS = <%= scope['pulpcore::allowed_import_path'] > ALLOWED_EXPORT_PATHS = <%= scope['pulpcore::allowed_export_path'] %>	
<b>Expected results:</b>  If changing the import and export path is allowed, then we will need a module for custom-hiera.yaml and satellite-installer parameter	
<b>Additional info:</b>  Tried the below parameters in hiera but not work after running the installer.	
1. cat /etc/foreman-installer/custom-hiera.yaml	
pulpcore::allowed_import_path: ["/mnt/test5", "/mnt/test6"] pulpcore::allowed_export_path: ["/mnt/test7"]	

---

## Associated revisions

---

### Revision c8ba0fe5 - 05/10/2022 07:31 PM - William Clark

Fixes #34882 - allow custom pulpcore import/export paths

## History

---

### #1 - 05/09/2022 10:53 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request [https://github.com/theforeman/puppet-foreman\\_proxy\\_content/pull/417](https://github.com/theforeman/puppet-foreman_proxy_content/pull/417) added

### #2 - 05/10/2022 07:31 PM - The Foreman Bot

- Fixed in Releases 3.3.0 added

### #3 - 05/10/2022 08:01 PM - William Clark

- Status changed from Ready For Testing to Closed

Applied in changeset [puppet-foreman\\_proxy\\_content|c8ba0fe5fc2d7e389c3983e8545601299954508a](#).