

## Installer - Feature #36037

### Manage Redis service when the cache store is set to Redis

02/02/2023 02:12 PM - Ewoud Kohl van Wijngaarden

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Ewoud Kohl van Wijngaarden	
<b>Category:</b>	Foreman modules	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 3.6.0
<b>Triaged:</b>	Yes	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	2165092	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/theforeman/puppet-foreman/pull/1109">https://github.com/theforeman/puppet-foreman/pull/1109</a>	
<b>Description</b>		
By default the Redis cache URL is hardcoded to <code>redis://localhost:8479/0</code> , unless specified explicitly. It would be better to automatically set up Redis and determine the port from that. We already have a Redis instance for Dynflow, so it wouldn't be much overhead.		

#### Associated revisions

##### Revision dfa6a869 - 02/16/2023 01:07 PM - Ewoud Kohl van Wijngaarden

Fixes #36037 - Manage Redis service for Redis cache

This automatically manages Redis when the cache store type is set to Redis, but no URLs have been provided. It's assumed that when a URL is provided that the service is managed in another way.

This ignores the edge case where the user wants to run it on localhost, but with a different database than 0.

#### History

##### #1 - 02/02/2023 02:17 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Ewoud Kohl van Wijngaarden
- Pull request <https://github.com/theforeman/puppet-foreman/pull/1109> added

##### #2 - 02/17/2023 11:10 AM - The Foreman Bot

- Fixed in Releases 3.6.0 added

##### #3 - 02/17/2023 12:01 PM - Ewoud Kohl van Wijngaarden

- Status changed from Ready For Testing to Closed

Applied in changeset [puppet-foreman|dfa6a869710b317157a225f4fa323dc196b1b738](#).

##### #4 - 02/28/2023 02:59 PM - Ewoud Kohl van Wijngaarden

- Triaged changed from No to Yes