

Installer - Bug #8915

The foreman-installer script exits without useful information when trusted_node_data = true

01/12/2015 03:23 PM - Trevor Vaughan

Status: Duplicate	
Priority: High	
Assignee:	
Category:	
Target version:	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>We are looking to integrate The Foreman into a pre-existing system and are having difficulties.</p> <p>First, the foreman-installer script exits with return code 25 and the following error message:</p> <pre>Could not get default values, check log file at /var/log/foreman-installer/foreman-installer.log f or more information</pre> <p>The foreman-installer.log file contains:</p> <pre>[ERROR 2015-01-12 20:11:49 main] Repeating errors encountered during run: [ERROR 2015-01-12 20:11:49 main] Could not get default values, cannot continue</pre> <p>If we remove the 'trusted_node_data = true' line from puppet.conf, the installer continues.</p> <p>Expectation: trusted_node_data should be allowed when using The Foreman installer.</p>	
Related issues:	
Blocked by Installer - Bug #8944: rename facts parameter in foreman puppet mo...	Closed 01/13/2015

History

#1 - 01/13/2015 07:42 PM - Anonymous

- Blocked by Bug #8944: rename facts parameter in foreman puppet module added

#2 - 02/10/2015 10:13 AM - Dominic Cleal

- Status changed from New to Duplicate

This should be resolved in Foreman 1.8 and current nightlies thanks to [#8944](#).